

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 February 2004 (19.02.2004)

PCT

(10) International Publication Number
WO 2004/014698 A1

(51) International Patent Classification⁷: B60R 9/06

(21) International Application Number:
PCT/IB2003/003535

(22) International Filing Date: 6 August 2003 (06.08.2003)

(25) Filing Language: Italian

(26) Publication Language: English

(30) Priority Data:
MO2002A000231 9 August 2002 (09.08.2002) IT

(71) Applicant (for all designated States except US): FLLI
MENABO' S.R.L. [IT/IT]; Via 8 Marzo, 3, I-42025
Cavriago (IT).

(72) Inventor; and

(75) Inventor/Applicant (for US only): MENABO',
Domenico [IT/IT]; Via Ruini, 3, I-42029 San Maur-
izio (IT).

(74) Agent: LUPPI, Luigi; Luppi Crugnola Bergamini & Part-
ners S.R.L., Viale Corassori, 54, I-41100 Modena (IT).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted
a patent (Rule 4.17(ii)) for the following designations AE,
AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA,
CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES,
FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,

[Continued on next page]

(54) Title: LOAD CARRIER FOR VEHICLES



(57) Abstract: An apparatus for transporting loads, suitable for being mounted on a vehicle (D), comprising first frame body means (2) and second frame body means (3), that are mutually coupled by hinge means (5) and are arranged for being associated with opposing edges (C, E) of a part (E) of vehicle (D) by anchoring means (30, 18), load supporting means (14) associated with said first and/or second frame body means (2, 3), characterised in that are provided fixing means (19) suitable for interacting with said anchoring means (16) and interposed between said frame body means (2, 3) and said anchoring means (16).

WO 2004/014698 A1



MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designation US
- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Load carrier for vehicles

The invention relates to a luggage carrier for vehicles, i. e. a device suitable for receiving loads, preferably applicable to the rear portion of said vehicles at a door or a boot
5 cowl, provided with an adjusting system that enables said luggage carrier to conform to vehicles with different sizes and shapes.

The rear luggage carriers available at present substantially differ one from the other on the basis of the technical
10 solutions chosen for adapting a same luggage carrier to the plurality of shapes and sizes of the attachment regions of the vehicles generally available on the market.

WO 00/76809 suggests a luggage carrier comprising frame sections mutually connected by means of telescopic tubes; in
15 this case, a variation of the length of the luggage carrier is obtained making the portions of the frame to telescopically slide one into the other, this enables to engage hook portions of opposed ends of each section with corresponding edge portions of the vehicle hatchback.

20 In the mounting and dismounting phases, the user is requested to apply a certain force for causing the sections to mutually slide as well as for blocking said sections in the desired position by means of a lever closing device, that results in a clear disadvantage.

25 A so structured device has short handling in use as well as a substantial complexity in fabrication due to the necessity to provide components (telescopic elements of the frame, closing lever) that increase fabrication time and fabrication costs.

Are also known luggage carrier for vehicle described for
30 example in US 5056699, US 6345748 e US 6286738, that are provided with a frame comprising a first part of frame and a second part of frame that are hinged one into the other.

The first part of the frame below ends with a couple of supporting elements arranged for being positioned on the rear

of the vehicle bumper or on the lower edge of the rear vehicle hatchback, thus actually impeding the opening of the vehicle hatchback after the luggage carrier has been mounted.

In an intermediate section of the second part of frame is
5 further hinged a resting clamp for resting on the rear window of the vehicle, or on the bonnet of the rear boot.

Elements for supporting a load, for example a bicycle, are hinged at the top of the second part of frame.

For fixing the luggage carrier to the vehicle it is necessary
10 to anchor luggage carrier by means of a plurality of belts that have to be appropriately stretched one by one by the operator.

Before stretching the belts, it is necessary to articulate, by acting on the hinges arranged between the first and the second
15 part and between the latter and the resting bracket, the relative parts of frame so as the resting elements and the resting bracket are correctly positioned on the parts of vehicle.

Furthermore, it is necessary, still manually acting, to
20 intervene on the hinges interposed between the second part of frame and the load supporting elements (forming, for example, a rack) so as to carry the latter in a position substantially suitable to receive the load.

Fixing the luggage carrier is particularly laborious, because
25 it is necessary to act to position and stretch individually the numerous belts, and this implies a remarkable time and energies loss.

At end, a further efforts is requested to assure a secure locking of the rack in a position suitable for receiving the
30 load, because the operator has to manually act on the locking devices provided in the known luggage carriers.

The luggage carriers of this kind, are furthermore constructionally complex, because it is necessary to arrange numerous components to obtain first and second parts of frame,

elements for receiving the load, as well as devices for blocking the latter in the use position.

An object of the present invention is to improve the luggage carriers for vehicles.

5 A further object is to provide the user with a luggage carrier that can be easily mounted and dismounted from a vehicle.

Another object is to provide a luggage carrier provided with an actuating device for anchoring on and dismounting from a vehicle that is easy to be reached.

10 A further other object is to simplify the manual operation required to the user during the phase of fitting the luggage carrier on the sizes and shapes of the vehicle whereon it is mounted.

A still further object is to reduce the number of components forming of the luggage carrier, thus reducing time and costs
15 of production.

The invention provides an apparatus for transporting loads, suitable for being mounted on a vehicle, comprising first frame body means and second frame body means, that are
20 mutually coupled by hinge means and are arranged for being associated with opposite edges of a part of vehicle by anchoring means, load supporting means associated with said first and/or second frame body means, characterised in that are provided fixing means suitable for interacting with said
25 anchoring means and interposed between said frame body means and said anchoring means.

The anchoring means comprises hooking elements suitable to wound a significant edge portion of said part of vehicle.

The fixing means are preferably interposed between the
30 anchoring means and the first frame body means. Still preferably, the fixing means can be obtained by using connecting members, flexible or not flexible - such strap, pierced strap (in particular metallic) - tie-rod, preferably of the screw type, toothed belts.

The connecting members can be coupled to stretching devices known in se, such: ratchets, windlass, stretchers, and similar.

After the opening angle comprised between first and second
5 frame body means has been manually regulated so as to fit the shape of the vehicle part on which the device has to mounted, and after the first and second frame body means has been blocked in their mutual position that define such angle, it is possible to act on the afore-said fixing means for stretching
10 the same, and thus assuring a stable positioning of the apparatus on the vehicle.

In this way, it is possible to mount in a safe manner the luggage carrier on a plurality of vehicles provided with different shapes and dimensions by simply acting on the fixing
15 means, that are moreover arranged in a position easy to be reached.

From this follows that the manual intervention requested to the user is substantially facilitated in relation to what happen in other models of known luggage carriers.

20 Advantageously the load supporting means can be obtained so as to form a single body with the frame body means.

In this way, when the frame means are positioned on the vehicle, the here above said supporting means is itself arranged in a suitable load receiving position and it has not
25 to be further regulated by the user.

This enables to further limit the manual intervention requested to the user for arranging the luggage carrier to be used.

Furthermore, the number of parts necessary for assembling the
30 luggage carrier is reduced.

The invention can be better understood with reference to the enclosed drawings, that illustrate some exemplifying and not restrictive embodiment forms thereof, in which:

Figure 1 is a perspective view of a luggage carrier; in the version using fixing means comprising pierced straps, mounted on the rear door of a vehicle;

Figure 2 is a side view of the luggage carrier in Figure 1, showing with continuous line the luggage carrier when the mounting have been finished, and with dashed line the same luggage carrier during mounting;

Figure 3 is an enlarged view of the fixing means shown in Figures 1 and 2;

Figure 4 is a perspective view of further version of a luggage carrier.

The Figure 1 shows a luggage carrier 1 mounted at the rear end of a vehicle D, represented by dashed line, and comprising a frame body 2 and a further frame body 3. The frame body 2 comprises a U-shaped portion 2', whose two ends extend over two arms 7, each one of which is provided with an extractable portion 8, provided with through holes 9; once the luggage carrier 1 has been assembled, the U-shaped portion 2' shows the arms 7 turned downwards; between the U-shaped portion 2' and the arms 7 there is defined an obtuse angle G, not shown. The U-shaped portion 2' contains, near each one of its parallel sides, a slip joint 5 comprising a pair of discs frontally toothed reciprocally seizing up.

The slip joint 5 is interposed between the frame body 2 and the further frame body 3, and enables to articulate the two afore-said frame bodies as well as to blocking in preset reciprocal angular position.

The extractable portion 8 can be received for a longer or shorter portion of its length into the arm 7 and can be fixed in the preset position by means of a bolt, not shown, suitable for being positioned at one of the through holes 9. Thus, the length of any arm 7 can be changed and in particular can be made suitable for being mounted on vehicle portions that, due to their extend, would be otherwise unreachable.

The extractable portion 8 further comprises an anchoring appendage 10, terminating with a curved end 11 suitable for hooking with a bottom edge E' of the rear door E or a of bonnet boot, not shown, of a vehicle D.

- 5 Near the ends of the arms 7 adjacent to the rear bumper, not shown, of the vehicle D, there is placed a C-shaped element 12, arranged so as to have its longer rectilinear portion facing in the opposed direction with respect to the rear door E. The C-shaped element 12 engages with each of the arms 7 by
10 means of a further 5', provided with a clutch 4', the latter comprising a knob 6. The knob 6 enables to reciprocally tighten the two discs of the clutch 4', so blocking the hinge 5' in the requested position. The hinge 5' enables the C-shaped element 12 to be moved from a retracted position H to
15 an extended position H', represented by dashed line. That enables to prevent that a particularly voluminous object mounted on the luggage carrier, for example a bicycle, can accidentally hit and then damage the surface of the rear door E or of the rear bumper, not shown, of the vehicle D.
- 20 The further frame body 3, as depicted in the Figures 1 to 3, has a further U-shaped portion 3', whose two ends extend, by means of two curved sections 13, over two brackets 13'; each of the brackets 13' defines with the U-shaped portion 3' a further obtuse angle G', not shown. Each of the brackets 13'
25 further contains a set of grooves 14a, suitable for being advantageously used as rack 14 whereon bicycles, having frame provided with central crossbar, can be received. With the rack 14 there is associated a tightening tape 14b suitable for holding in position the frame crossbar, received in every
30 groove 14a.

The slip joints 5 are arranged at the intersection between the two portions of the further frame body 3 comprised between the two curved sections 13 and the two racks 14.

The further frame body 3 receives in its further U-shaped portion 3' at least a resting element 15, preferably in form of resilient cylinder having smooth surface; by means of the resting element 15 the further frame body 3 can be applied on the rear door E without damaging the external surface of the latter.

On each on of the two ends of the further U-shaped portion 3' of the further frame body 3 is arranged, in proximity of a median segment M, a fixing group 19 (depicted in detail in Figure 3) defining fixing means. Each fixing group 19 comprises dragging means 23 received in seat means 34, being the afore-said seat means 34 delimited by a couple of sidewalls 24, 24' that have convex outline and whose relative bases are integral with an intermediate plate 35. The intermediate plate 35 is made integral with the median segment M by means of a washer bolt 36. The dragging means 23 comprises in turn a shell 25, with an approximately C-shaped section, that is made integral with the couple of sidewalls 24, 24' by means of a plurality of protruding elements 25'. The shell 25 internally receives an operating screw 26, vertically oriented and provided at its end opposed to the median plate 35 with a nut 27. The operating screw 26 engages with a toothed wheel 29 supported by the sidewalls 24, 24' and provided with tooth 29' engaged in equidistant holes 30' obtained in a pierced portion 30' of a strap 30 that is interposed between the toothed wheel 29 of the dragging means 23 and the further frame body 3'.

The strap 30 comprises a pierced portion 30' and a unpierced portion 31 partially covered by an anti-abrasive sheathing 16. The free end 31' of the unpierced portion 31 is integral with a curved flake 18, suitable to hook to a upper edge C of the rear door E or of a bonnet boot, not shown, of a vehicle D.

By acting on the nut 27, it is possible to rotate the operating screw 26 about its axis, and in this way to operate

the toothed wheel 29. The tooth 29' of the toothed wheel 29 then engages in sequence in a plurality of holes 30'' contained in the pierced portion 30' of the strap 30, thus making the same strap 30 to slide. The sliding direction of the pierced strap 30 is determined by the rotation direction
5 given to the operating screw 26 by means of the nut 27..

By rotating the nut 27 in a direction, the strap 30 is moved along a direction F away from the curved flake 18 and then stretched, this enables to firmly anchor the curved flake 18
10 to the bodywork of the vehicle D and to firmly maintain the luggage carrier 1 in a position suitable to be used.

Naturally, by rotating the nut 27 in an opposite direction, the pierced strap 30 is moved in a direction F oriented towards the curved flake 18. In this way, the strap 30 is
15 loosen, this enables the curved flake 18 to be unhooked from the upper edge C of the rear door E or of a bonnet boot, not shown, of a vehicle D and to subsequently to remove the luggage carrier 1.

With reference to Figure 4, a preferred version of the luggage carrier 1 is provided, in which the further frame body 3a
20 comprises, instead of the brackets 14, another further U-shaped portion 3b extending, at both the ends, over an L-shaped loading element 27. Each one of the L-shaped loading elements 27 comprises a vertical bar 28a and a horizontal bar
25 28b, mutually connected at right angle. Each one of the vertical rod 28a engages with the frame body 2 by means of the slip joint 5 previously described. The two horizontal bars 28b receive a pair of profiled elements 29, orthogonally arranged with respect to said horizontal bars 28b and having a roughly
30 C-shaped section.

With such advantageous version of the luggage carrier 1 can be transported bicycles also having a frame unprovided with central crossbar, such as for example the ladies' bicycles.

CLAIMS

1. Apparatus for transporting loads, suitable for being mounted on a vehicle (D), comprising first frame body means (2) and second frame body means (3), that are mutually coupled by hinge means (5) and are arranged for being associated with opposite edges (C, E) of a part (E) of vehicle (D) by anchoring means (30, 18), load supporting means (14) associated with said first and/or second frame body means (2, 3), characterised in that, are provided fixing means (19) suitable for interacting with said anchoring means (16) and interposed between said frame body means (2, 3) and said anchoring means (16).
2. Apparatus according to claim 1, wherein said load supporting means (14) forms a single body with said first and/or second frame body means (2, 3).
3. Apparatus according to claim 2, wherein said load supporting means (14) are obtained on prolongations of said second frame body means (3) farther on said hinge means (5).
4. Apparatus according to any one of the preceding claims, wherein said first frame body means (2) comprises a portion (2') U-shaped.
5. Apparatus according to claim 4, wherein said U-shaped portion (2') extends on arm means (7).
6. Apparatus according to claim 5, wherein said U-shaped portion (2') and said arm means (7) are so arranged to define an obtuse angle (G).
7. Apparatus according to any one of claims 5, or 6, wherein said arm means (7) finishes with extremity appendage anchoring means (10).
8. Apparatus according to any one of claims 5 to 7, wherein said arm means (7) comprises telescopic portion means (8).

9. Apparatus according to any one of claims 5 to 8, wherein said arm means (7) supports in adjustable manner end portion of load distancing means (12) C-shaped.
- 5 10. Apparatus according to any one of preceding claims, wherein said second frame body means (3) comprises a further portion (3') U-shaped.
11. Apparatus according to claim 10, wherein said further portion (3') U-shaped comprises resting means (25) in shock resistant material.
- 10 12. Apparatus according to any one of preceding claims, wherein said load supporting means (14) comprises brackets means (13') arranged on the prolongation of said further portion (3') U-shaped.
13. Apparatus according to claim 12, wherein said brackets means (13') and said further portion (3') U-shaped are so arranged to form a further obtuse angle (G).
14. Apparatus according to claim 12, or 13, wherein said brackets means (13') receive rack means (14).
- 15 15. Apparatus according to claim 12, wherein said brackets means (13') extends on load means (27) L-shaped, comprising a vertical bar means (28a) and a horizontal bar means (28b), angularly reciprocally connected.
16. Apparatus according to claim 15, wherein said horizontal bar means (28b) receives profiled elements (29), transversally arranged in relation to said horizontal bar means (28b).
- 25 17. Apparatus according to any one of the preceding claims, wherein said fixing means (19) are interposed between said anchoring means (16) and said second frame body means (3).
- 30 18. Apparatus according to any one of the preceding claims, wherein said fixing means (19) are selected among a group comprising: flexible connecting members,

non-flexible connecting members, straps, screw tie-rod, windlass, ratchets, toothed straps.

19. Apparatus according to any one of the preceding claims, wherein said fixing means (19) comprises a straps (30) provided with holes (30'') in which engage tooth (29') of a toothed wheel (29) that can be rotated by means of an operating screw (26).

1/4




Fig. 1

2/4




Fig. 2

3/4




Fig.3

4/4




Fig.4

INTERNATIONAL SEARCH REPORT

PCT/IB 03/03535

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B60R9/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B60R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
E	WO 03 072396 A (MENABO) 4 September 2003 (2003-09-04) the whole document	1-18
X	US 3 927 811 A (NUSSBAUM) 23 December 1975 (1975-12-23) abstract	1-7, 10-13, 17,18
A	US 3 710 999 A (ALLEN) 16 January 1973 (1973-01-16)	
A	US 5 435 472 A (ALLEN) 25 July 1995 (1995-07-25)	
A	US 4 709 840 A (ALLEN) 1 December 1987 (1987-12-01)	
	-/-	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

G document member of the same patent family

Date of the actual completion of the international search

7 November 2003

Date of mailing of the international search report

14/11/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Knops, J

INTERNATIONAL SEARCH REPORT

PCT/IB 03/03535

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 336 897 A (LUCK) 29 June 1982 (1982-06-29)	
A	FR 2 668 435 A (MOTTEZ) 30 Apr 11 1992 (1992-04-30)	

INTERNATIONAL SEARCH REPORT

PCT/IB 03/03535

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 03072396	A	04-09-2003	WO 03072396 A1	04-09-2003
US 3927811	A	23-12-1975	NONE	
US 3710999	A	16-01-1973	NL 7115228 A	09-05-1972
US 5435472	A	25-07-1995	US 5598960 A	04-02-1997
US 4709840	A	01-12-1987	NONE	
US 4336897	A	29-06-1982	NONE	
FR 2668435	A	30-04-1992	FR 2668435 A1	30-04-1992

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.